TECHNICAL DATA SHEET

Crimscent

GAS ALARM PANEL – 4 ZONE

Description

The CI-GCP-4Z is an 4-Zone control panel. It is indicating equipment forms the central part of a gas detection and alarm system. The 4-wire is compatible with CI-GCP-4Z devices. And it is the central part of conventional gas alarm system, designed for applications requiring gas leak detector, bell, manual pull stations, and sprinkler supervision. Each zone can be disabled by a button.



- Operates on 230 V AC, 50 Hz AC supply
- Battery backup with built in charger
- Gas leak, fault status in unambiguous colored LED indications
- 16 x 2 line dot matrix LCD display
- Zone wise fire, open, short LED indications.
- External switches to test each zone leak, open, short status manually
- External switch for reset, Silence, Lamp test.
- Zone isolation facility with loop voltage cutoff.
- Relay O/P for actuators.
- Mains on, System On, Charger on, visual indications.
- Battery Low Common leak indications
- Auto dialer attachable facility
- Enough inside space for battery
- Attachable with all types of detectors.

Specification:

MODEL NO.	**CI – GCP-4Z**
Operating voltage Range	AC 220v 50Hz ± 10%, DC 24 v 1.5 amp
Operating Temperature	-0º C to 50º C
Operating Humidity	95% (non-condensing)
Hooter Output	1 A (24v DC)
EOL	4k7 ohm, 1 per zone
Construction	1.8 mm CRCA sheet duly power coated
Dimension	H 245mm * W 315mm * D 90mm
Color	Caramel White

Address :
Factory Address : 216,217, Hasti Industrial Premises,Mahape MIDC,Navi Mumbai-400710
Contact Details : +91-8169185379/ +91-9594649625
Email Id : info@crimscent.com,pankaj@crimscent.com