Crimscent

# GAS CONTROL PANEL GCP- 6600




Try Pitch

## Technical Specifications :

- Operating Voltage: 230VAC
- Display : HMI (Also available in LCD display)
- Enclosure: Flameproof - Flameproof Enclosure(MS housing optional)
- Size: 1000mm X 600mm X 1000mm
- Weight: 35 kg Approx
- 16 cable entries
- Buttons : RST, ACK, TEST, SCRN
- Output Signal: Industry standard 4 - 20 mA sourcing (Cable load driving capacity: 650 ohm maximum)
  RS-485 (MODBUS) on 4-core cable
- Operating Temperature: 0ºC to 65 deg C
- Operating Pressure Range: Ambient +/-10%
- Operating Humidity Range: 0-95% RH (non-condensing)
- Ingress Protection: IP66)
- Toughened Glass Window Provision
- Mounting: Suitable for mounting on walls, poles, or similar support
- Exd certified cable glands available on request




Try Pitch

# Additional Features :

Expanding the features of your Gas Control Panel GCP-6600 can enhance its appeal to a wider range of clients and applications. Here are some additional features you may consider, depending on client requirements:

1. In-built audio visual hooter
2. **Data logging:** As standard, with gas concentration, date & time
3. **Data Transfer/Print:** USB (wired) communication from detector to computer
4. GSM dialler : SMS, Email and Phone calls to upto 15 nos
5. LCD Display

# We also provide customized solutions for our gas leak controller after understanding our client’s requirements.

Try Pitch

For concerns and complaints, contact us at : www.crimscent.com or call us at : +91-8169185739/ 9594649625

Visit us : 132,133,Ganesh Building,Sector-1,Ghansoli-400701

Mail us : info@crimscent.com /pankaj@crimscent.com




Try Pitch